

DCDC

RSD-200

ATOMBOTIX



Space-Saving, Rack-Ready Design



1U low profile (39 mm)

Enhanced Safety



Ultra-High Voltage Isolation
4000VDC I/O isolation

Extra Load Capacity



Supports 150% peak current for
high inrush or startup demands

Optimized for AGV & AMR



EN50155 railway standard
guarantee smooth performance in mobility

Versatile Input Flexibility



2:1 wide input range

Comprehensive Protection



Short circuit / Overload / Over
voltage / Over temp./ Input
reverse polarity

pec		DDR-240B-24	DDR-240B-48	DDR-240C-24
Wattage	W	240	240	240
Output Current	A	0-10	0-5	0-10
Output Voltage	V	24	48	24
Output Voltage Options		Single	Single	Single
DC output adjustment		24-28	48-56	24-28
Dimensions		40 x 125.2 x 113.5	40 x 125.2 x 113.5	40 x 125.2 x 113.5
Working Temperature	°C	-40-70		
Safety Standards		IEC 62368-1 (LVD, except for 67.2-154VIN) approved, EAC TP TC 004 approved; Design refer to UL508		
EMC Standards		Compliance to EN55032, EN61000-3-3. Compliance to EN55024, EN61000-6-2 (EN50082-2), EN61000-4-2,3,4,5,6,8. Compliance to EN45545-2 for fire protection ; Meet EN50155 / IEC60571 including IEC61373 for shock & vibration EN50121-3-2 for EMC		

		DDR-240C-48	DDR-240D-24	DDR-240D-48
Wattage	W	240	240	240
Output Current	A	0-5	0-10	0-5
Output Voltage	V	48	24	48
Output Voltage Options		Single	Single	Single
DC output adjustment		48-56	24-28	48-56
Dimensions		40x 125.2x 113.5	40x 125.2x 113.5	40x 125.2x 113.5
Working Temperature	°C	-40-70		
Safety Standards		IEC 62368-1 (LVD, except for 67.2-154VIN) approved, EAC TP TC 004 approved; Design refer to UL508		
EMC Standards		Compliance to EN55032, EN61000-3-3. Compliance to EN55024, EN61000-6-2 (EN50082-2), EN61000-4-2,3,4,5,6,8. Compliance to EN45545-2 for fire protection ; Meet EN50155 / IEC60571 including IEC61373 for shock & vibration EN50121-3-2 for EMC		

Case No.265A-D Unit:mm

