

Warning Light Series

AB-L50 & AB-WL-1BR30W

ATOMBOTIX



Durable & Long-Lasting



Supports high-frequency output with an extended service life, ensuring reliable long-term use

Stable Performance



Delivers consistent power output and performs reliably across a wide range of environmental conditions

Easy Installation



Secured with screws and bolts for fast, stable, and hassle-free mounting

Robust Structure



Features a high-quality alloy base that offers excellent strength and durability, making it resistant to damage



No.	01	02	03
Model	AB-L50	AB-SL50	AB-TL50
Flash Frequency	63-65 times/min	63-65 times/min	63-65 times/min
Protection Class	IP65 without buzzer, IP30 with buzzer	IP53	IP53
Operating Temperature	-20 - 45 °C	-20 - 45 °C	-20 - 45 °C
Lamp Life	50,000 h	50,000 h	50,000 h
Mounting Method	Mounting by nut	Mounting by screw	Mounting by screw
Material	Lamp body: Aluminum alloy; Lampshade: PC; Base: Aluminum alloy	Lamp Body: Acrylic,PC; Base: Aluminum	Lamp Body: Aluminum+PC; Base: Reinforced nylon

04



05



06



07



08



09



No.	04	05	06
Model	AB-WL-1BR30W	AB-WL-1BR18W	AB-WL-1BR10W-mini
Power	30 W	18 W	10 W
Dimension	155 x 43 x 60 mm	160 x 43 x 65 mm	62 x 53 x 57 mm
Working Voltage	DC 12-80 V	DC 12-80 V	DC 12-80 V
Shell Material	Aluminium alloy	Aluminium alloy	Aluminium alloy
Cycle Line	30,000 hs	30,000 hs	30,000 hs
Weight	1000 g	1000 g	1000 g
No.	07	08	09
Model	AB-WL-UBR10W-mini	AB-WL-UBR30W	AB-WL-SBR18W-mini series
Power	10 W	30 W	18 W
Dimension	62 x 54 x 50 mm	130 x 120 x 53 mm	62 x 62 x 76 mm
Working Voltage	DC 12-110 V	DC 12-110 V	DC 12-80 V
Shell Material	Aluminium alloy	Aluminium alloy	Aluminium alloy
Cycle Line	30,000 hs	50,000 hs	30,000 hs
Weight	1000 g	1000 g	1000 g

