

Customized Button

AB-MS/LS-N/D

ATOMBOTIX



Versatile Configuration



Available in multiple colors and circuit options, allowing customization for exclusive switch designs

Heat Resistant & Flame Retardant



Made from high-quality flame-retardant PC material to ensure safety and reliability during frequent

Self-Cleaning Contacts



Features automatic contact cleaning to reduce dust and oxidation, ensuring stable electrical performance

Durable & Cost-Effective



Long service life with excellent cost-performance ratio

	AB-MS-Nx	AB-LS-Nx	AB-MS-Dx	AB-LS-Dx	AB-MS-OC	AB-LS-OC
Rated Voltage	12V/24V	12V/24V	12V/24V	12V/24V	12V/24V	12V/24V
Heating Current	10A	10A	10A	10A	10A	10A
Operating Frequency	1200 times/h	1200 times/h	1200 times/h	1200 times/h	1200 times/h	1200 times/h
Operating Temperature	-25 - 55 °C	-25 - 55 °C	-25 - 55 °C	-25 - 55 °C	-25 -55 °C	-25 - 55 °C
Storage Temperature	-30 - 70 °C	-30 - 70 °C	-30 - 70 °C	-30 - 70 °C	-30 - 70 °C	-30 - 70 °C
Operating Humidity	45% - 85% RH	45% - 85% RH	45% - 85% RH	45% - 85% RH	45% - 85% RH	45% - 85% RH
IP Ratings	IP54	IP54	IP54	IP54	IP54	IP54
Certification	CE	CE	CE	CE	CE	CE
LED	Optional	Optional	Optional	Optional	Optional	Optional
Contact Specification	NC/NO	NC/NO	2*NC/2*NO	2*NC/2*NO	NC&NO	NC&NO
Operating Characteristics	Momentary Switch	Latching Switch	Momentary Switch	Latching Switch	Momentary Switch	Latching Switch

