

PLATFORM LIFTER

AB-FLB-PL04

ATOMBOTIX



Multiple Safety Protections



Have multiple level safety protections including front and rear laser detection, front and rear binocular detection, 360 degree anti collision edges, and emergency stop buttons

Versatile Material Handling



Capable of lifting, transporting, and rotating loads up to 400 kg, with customizable load attachments to suit various application scenarios

Equipment Status Indication



Indicate various states of the vehicle through multiple lighting effects

Wireless Network Communication



Support WiFi and 5G network communication, enabling unobstructed operation within the network coverage area

Autonomous Positioning and Navigation



Achieve precise positioning through technologies such as QR codes, laser SLAM, and texture

Flexible Motion Control



Employ two - wheel differential speed drive to support forward, backward, and rotational motion controls, ensuring smooth operation

Intelligent Power Management



Support multi - level power threshold control. It automatically recharges when the power is low and resumes work after charging is complete

Model	AB-FLB-PL04
Feature	
Drive Mode	Differential drive of two wheels
Dimensions	778 × 540 × 255 mm
Rotation Diameter	778 mm
Self-weight	98 kg
Rated Load	400 kg
Chassis Ground Clearance	25 mm
Lifting Panel Size	710 × 500 mm
Lifting Height	60 mm

Performances	
Rated Operating Speed (Rated Load / No Load)	1.5 m/s / 1.9 m/s
Acceleration (Rated Load / No Load)	0.3 m/s ² / 0.6 m/s ²
Rotation Speed (Full Load / No Load)	100°/s / 200°/s
Battery	
Battery Type	Lithium iron phosphate
Capacity / Rated Voltage	16 Ah / 48 V
Charge-Discharge Cycle Times	1,500 times
Rated Working Condition Endurance Time	6-8 h
Charging Time After Complete Discharge	≤ 1.5 h
Communication Protocol	CAN/RS485
Other Parameters	
Navigation Mode	Laser SLAM or 2D code
Front Laser Obstacle Avoidance (Quantity / Installation Height)	1 piece / 220 mm
Opening Angle	250°
Emergency Stop Buttons	2 pieces (front and rear each 1)
Contact Protection	Piezoelectric edge switch
Acoustic-Optic Alarm	Standard
Chassis Damping Mode	Two-stage floating chassis
Climbing Capacity	≤5% / 3°
Step Capacity	≤5 mm
Gutter Crossing Capacity	≤30 mm
Signal	Supports dual-band Wi-Fi (2.4 GHz and 5 GHz), with wireless signal strength ≥ -70 dBm.
Humidity	Relative humidity 10%-90% without condensation
Temperature	Working area: -10°C - 45°C Charging area: 0°C - 45°C

